

# 12"

## MACH 120

One piece top-adaptor reduces internal parts. No make up required. External N.R.V. for easy maintenance.

Simplified piston geometry for improved balance and location within the cylinder.

Revised chamber volumes and cycle timing to optimize performance.

A100-15/SD12 shank reduces contact stresses and wear rates.




The Mach 120 accepts A100-15 (SD12) shank bits and its optimum performance is reached at air pressures of 200psi (14 bar) and above. The Mach 120 has a one piece top-adaptor with N.R.V. (Non-Return-Valve) fitted for easy inspection and service, with integral finger to reduce maintenance and eliminate shimming which increases service intervals. Mach 120 has no liner which increases the 140 kg piston's blow energy and reduces parts required. This hammer is suitable for use with overburden systems.

Suitable for operation at air pressures of 100 - 435 psi (7 - 30 bar).


Drilling diameters of 300 - 445mm (11 7/8 - 17 1/2").

### Air Consumption



### Available Shanks

Sandvik Mission A100-15/SD12



## Hammer Overview

<b>Hammer Type</b>	<b>Mach 120</b>
<b>Part Number</b>	<b>600108</b>
Shank	Sandvik Mission
	A100-15 / SD12
Top Thread	6 .5/8" Api Reg Pin
Flat Hammer Size	N/A
Weight	614 Kg
Outside Diameter	273mm (10.748")
Make Up Length	1667mm (65.629")
Recommended Minimum Thrust	1600 Kg (3520 Lbs)
Recommended Maximum Thrust	3500 Kg (7700 Lbs)

## Parts List

Hammer Type		Mach120		
Shank		A100-15/SD12	SK12	RK19
Model Number		600108	Contents	
Item	Description	Part Number	Quantities	
1	Lifting Cap	602354	-	-
2	Circlip	777001	2	2
3	O'Ring	768133	2	2
4	N.R.V. Seat	602286	-	1
5	Non Return Valve	602288	-	1
6	N.R.V. Spring	760055	2	2
7	Top-Adaptor	602639	-	-
8	O'Ring	768137	2	2
9	O'Ring	768137	2	2
10	Top-Adaptor Spacer	602366	1	1
11	Cylinder	602013	-	-
12	Piston	602047	-	-
13	Snap Ring	783021	2	2
14	Containment Band	768105	-	-
15	Bit Retaining Ring	602102	-	1
16	Chuck Spacer	602366	1	1
17	Chuck	602052	-	1
18	End Cap	741035	-	-
SK	Service Kit	SK12		
RK	Repair Kit	RK19		
	Foot Valve	601811		
	F/V Tool - Body	601812		
	F/V Tool - Pusher	601813		

## Drill Bits

Part Number	Diameter		Face		Buttons Qty	Over Size	Weight (Kg)
	mm	Inch	Design	Type			
<b>Halco/ Sandvik Mission A100-15/SD12 Shank</b>							
650874	300	11.7/8	Convex	Domed	29 x 20mm		138
650383	311	12.1/4	Concave	Domed	31 x 20mm		133.5
650988	381	15	Concave	Domed	65 x 20mm D / 18 x 16mm W		208
653138	406	16	Concave	Domed	74 x 20mm D / 18 x 16mm W		210
650376	445	17.1/2	Concave	Domed	79 x 20mm	Y	245

Halco Rock Tools  
Quality Management System  
is Certified to ISO9001: 2008  
Certificate No: LRQ 0850659



West lane, Southowram, Halifax, HX3 9TW

Tel: + 44 (0) 1422 399900, Fax: + 44 (0) 1422 330186

Email: salesuk@halcorocktools.com • salesusa@halcorocktools.com • salesaus@halcorocktools.com

halcorocktools.com