

Challenger_® 125 Down Hole Hammer

FEATURES

- For use in any hard rock application
- Valveless down hole hammer design
- Designed to operate at pressures to 250 PSI (17.0 Bar)
- Hardened non-ported piston case
- Plate drive system to eliminate spline wear and galling
- Suitable for drilling oil & gas wells, water wells, piling holes, elevator shaft holes and other construction jobs where large volume rock excavation is required

AIR CONSUMPTION



SPECIFICATIONS

Diameter	10-3/4"	273 mm
Bore	9-1/4"	235 mm
Stroke	5"	127 mm
Weight (Hammer only)	1434 lbs.	652 kg
Length (Shoulder to Shoulder)	74"	188 cm
Length (Shoulder to Bit Face)	83"	211 cm
A.P.I. Reg. Threads	6-5/8	

- 1150 blows per minute at 250 PSI (17.0 Bar)
- Suitable for drilling holes from 12-1/4" to 20" (311 mm to 508 mm) in diameter
- Accepts N125 bit shank



Down Hole Button Bits

Challenger _® 125	DIAMETER inches (millimeters)		WEIGHT* pounds (kil	ograms)	FACES AVAILABLE
	12-1/4"	(312 mm)	433 lbs.	(197 kg)	Concave
	12-3/8"	(315 mm)	437 lbs.	(199 kg)	
	13"	(331 mm)	450 lbs.	(205 kg)	
	14"	(356 mm)	509 lbs.	(231 kg)	
	15"	(381 mm)	533 lbs.	(242 kg)	
	16″	(406 mm)	581 lbs.	(264 kg)	
<u> U]-U_J-U_J-U_U</u>	17-1/2"	(445 mm)	619 lbs.	(281 kg)	
	18"	(457 mm)	646 lbs.	(293 kg)	
	19"	(483 mm)	781 lbs.	(354 kg)	
	20"	(508 mm)	833 lbs.	(378 kg)	
			* Bit weights	are approximate	

FEATURES

N125 Bit Shank

- Concave face design for advanced hole cleaning capabilities
- 3/4" (19 mm) diameter carbide buttons throughout face
- Several grades and types of carbide are available
- Significantly larger spline area for exceptional strength and transfer of torque
- Plate drive system for increased spline life
- Side wear buttons are available as an option
- Other bit sizes may be available upon request

For More Information Contact:								
Northeast USA Mid		Mid-Atl	Aid-Atlantic USA Appalac		chian USA Southea		Hay ast USA 79-4834	
Virginia Lenox Western USA (325) 456-0695	Kathy W Oil & Western (325) 450	Gas 1 USA	Bruce F U.S. Cons Latin Aı (860) 23	struction merica	Chris Europe - <i>N</i> Africa +44 (0) 778	\iddle East - India	Ian Speer Australia +61 (0) 400 077 165	