BAROID PARLLIBURTON

CON DET®

Wetting Agent

Description

CON DET[®] wetting agent is a proprietary blend of anionic surfactants is specially formulated for use in fresh water, salt water, and in low-solids drilling fluids.

Applications/Functions

The use of CON DET wetting agent can promote the following:

- Keep the drill bit clean
- Slow breakup of cuttings while being transported from bit to surface
- Counteract the sticking tendencies of clays, thereby reducing wall packing, bit balling, booting-off, and formation of mud rings
- · Settling of cuttings at the surface in low solids fluid systems

Advantages

- Effective in low concentrations
- Easy to mix with water
- Biodegradable
- Compatible with other Baroid products

Typical Properties

•	Appearance	Clear red liquid
•	Specific gravity	1.03
•	pH (1 % solution)	8.9
•	Flash point, PMCC	210°F (99°C)
•	Pour point	28°F (-2.2°C)

Recommended Treatment

Approximate Amounts of CON DET Wetting Agent Added to Water			
Desired Condition/Result	Amount/ 100 gal	Amount/ bbl	Liters/m ³
To promote bit cleaning and to settle cuttings	2 – 4 pints	1 – 2 pints	2 – 5 liters
To reduce stickiness of clays	1 – 6 quarts	1 – 3 quarts	5 – 12 liters

Packaging

CON DET® wetting agent is packaged in 5-gal (19-liters) plastic containers.

Availability

CON DET wetting agent can be purchased through any Baroid Industrial Drilling Products Retailer. To locate the Baroid IDP retailer nearest you contact the Customer Service Department in Houston or your are IDP Sales Representative.

Baroid Industrial Drilling Products

Product Service Line, Halliburton

3000 N. Sam Houston Pkwy E.

Houston, TX 77032

 Customer Service
 (800) 735-6075 Toll Free
 (281) 871-4612

 Technical Service
 (877) 379-7412 Toll Free
 (281) 871-4613