KOPR-KOTE® TOOL JOINT & DRILL COLLAR COMPOUND

DESCRIPTION

KOPR-KOTE® drill collar and tool joint compound is a premium-quality, unleaded compound containing copper flake, graphite, and other natural extreme pressure and antiwear additives. **KOPR-KOTE's** solids package is formulated to prevent excessive circumferential makeup by increasing the coefficient of friction under compressive forces. As stress levels rise above 50% of yield, the friction factor increases, limiting downhole makeup. Full hydraulic joint efficiency is maintained allowing joint shoulder faces to mate completely without standoff or deformation. **For invert or high-pH muds, use Jet-Lube EXTREME™**.

Not classified as marine pollutant - DOT Approval CA2004080025

- NSF Registered H2 (No. 120923)
- · Contains no lead or zinc.
- Extreme pressure additives provide additional protection against seizing and galling and allow consistent makeup.
- Aluminum complex grease base protects against rust and corrosion.
- · Sticks to wet joints.
- · Unequaled resistance to makeup downhole.
- · Available in Arctic, Thermal and Specialty grades.
- Approved by NAM/Shell for under-balanced drilling applications.
- · Conforms to assembly bill 1953

SERVICE RATING: 0°F (-18°C) TO 450° (232°C)

PRODUCT CHARACTERISTICS

	Thickener	Aluminum Complex
•	Fluid Type	Petroleum
	Dropping Point	450°F (232°C)
	(ASTM D-2265)	
	Specific Gravity	1.15
	Density (lb/gal)	9.6
;	Oil Separation (ASTM D-6184)	<3.0
	WT. % Loss @ 212°F (100°C)	
,	Flash Point (ASTM D-92)	>430°F (221°C)
	NLGI Grade	1
	Penetration @ 77°F	310 - 330
	(ASTM D-217)	
	Copper Strip Corrosion	1A, typical

800, typical

PACKAGING

(ASTM D-4048)

Weld Point, kaf

4-Ball (ASTM D-2596)

Code No.	Container Size	Shipping Wt.
10023	1 gal.	11 lb.
10012	2 gal.	20 lb.
10015	5 gal.	52 lb.
10024	15 gal.	152 lb.
10029	50 gal.	514 lb.

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

CORPORATE LOCATIONS

Houston, Texas-World Headquarters

Maidenhead, England

Edmonton, Canada



JET-LUBE, INC. 4849 HOMESTEAD RD., SUITE 232 HOUSTON, TX 77028 WATS: 800-538-5823
PHONE: 713-670-5700
FAX: 713-678-4604
sales@jetlube.com
www.jetlube.com