

Patriot_® 50 **Down Hole** Hammer

FEATURES

- Outdistances competitive hammers in both speed and longevity
- Simplified hammer design with less internal components
- Drills at high frequency to provide less vibration and smooth operation
- More efficient design requires less air which equals fuel savings
- Designed to operate at pressures to 500 PSI (34.5 BAR)
- Ability to drill efficiently against high heads of water

AIR CONSUMPTION

DRILL PRESSURE (BAR) 13.6 20.4 27.6 1600 755 661 1400 566 1200 1000 472 378 S 800 600 283 189 400 200 1) SOLID CHOKE (2) 1/8 (3.2mm) CHOKE (3) 3/16 (4.8mm) CHOKE

300

DRILL PRESSURE (PSI)

200

400

500

(4) 1/4 (6.4mm) CHOKE

SPECIFICATIONS

Diameter	4-7/8"	124 mm
Bore	4"	102 mm
Stroke	3-1/2"	89 mm
Weight (Hammer only)	140 lbs.	63 kg
Length (Shoulder to Shoulder)	36-7/16"	93 cm
Length (Shoulder to Bit Face)	40-1/8"	102 cm
A.P.I. Reg. Threads	3-1/2	

- 1950 blows per minute at 350 PSI (23.8 BAR)
- Drills holes from 5-1/2" to 6-1/8" (140 mm 156 mm) in diameter
- Accepts QL50 bit shank



646 Thompson Road • Thompson, CT 06277 USA
Phone: (860) 923-9551 • Fax: (860) 923-2617
E-mail: numa@numahammers.com
www.numahammers.com

Down Hole Button Bits

Patriot_® 50

QL50 Bit Shank


DIAMETER inches (millimeters)

WEIGHT* pounds (kilograms)

F	AC	ES	A۱	/AI	LA	BL	E


5-1/2"	(140 mm)	33
5-3/4"	(146 mm)	34
6"	(152 mm)	36
6-1/8"	(156 mm)	36





* Bit weights are approximate

Flat



FEATURES

- 5/8" (16 mm) diameter carbide gage buttons
- Chipways designed for faster hole cleaning
- Carbide buttons positioned for better fracture of rock providing faster penetration rates
- Several grades and types of carbide are available
- Other bit sizes may be available upon request

For More Information Contact:

Bob LancasterTed FoustCarl ChidesterJeff HayNortheast USAMid-Atlantic USAAppalachian USASoutheast USA(860) 933-1715(717) 579-7809(304) 203-2408(478) 279-4834

Virginia Lenox Western USA (325) 456-0695 Kathy Wagoner Oil & Gas Western USA (325) 456-0407 Bruce Palmer U.S. Construction Latin America (860) 234-4823

Chris Beare Europe - Middle East Africa - India +44 (0) 7785 934 361 Ian Speer Australia +61 (0) 400 077 165