



Safety Tech Outrigger Pads deliver the safety, quality and performance you expect from the industry leader.

Stock Models

MODEL	LOAD CAPACITY		WIDTH	LENGTH	HEIGHT	WEIGHT	SQ.IN.
	VERTICAL	45 DEGREE					
PAD151575	40,000# (KG20,412)	18,000# (KG9,072)	15" (C38.1)	15" (C38.1)	.75" (C1.905)	5.5# (KG4.40)	225 (CT1,451.70)
PAD18181	55,000# (KG24,948)	30,000# (KG13,608)	18" (C45.72)	18" (C45.72)	1" (C2.54)	11.0# (KG4.99)	324 (CT2,090.45)
PAD24241	60,000# (KG27,216)	35,000# (KG15,876)	24" (C60.96)	24" (C60.96)	1" (C2.54)	20.0# (KG9.07)	576 (CT3,761.35)
PAD24242	62,000# (KG28,123)	40,000# (KG18,144)	24" (C60.96)	24" (C60.96)	2" (C5.08)	38.0# (KG17.24)	576 (CT3,761.35)
PAD30301	81,000# (KG36,741)	41,000# (KG18,597.6)	30" (C76.2)	30" (C76.2)	1" (C2.54)	31.0# (KG14.06)	900 (CT5,806.8)
PAD36361	93,000# (KG42,184.8)	43,000# (KG19,504.8)	36" (C91.44)	36" (C91.44)	1" (C2.54)	45.0# (KG20.41)	1296 (CT8,361.79)
PAD48481	135,000# (KG61,236)	52,000# (KG23,587.2)	48" (C121.92)	48" (C121.92)	1" (C2.54)	80.0# (KG36.29)	2304 (CT14,865.4)
PAD30302	85,000# (KG38,556)	43,000# (KG19,504.8)	30" (C76.2)	30" (C76.2)	2" (C5.08)	62.0# (KG28.12)	900 (CT5,806.8)
PAD36362	98,000# (KG44,252.8)	45,000# (KG20,412)	36" (C91.44)	36" (C91.44)	2" (C5.08)	90.0# (KG40.83)	1296 (CT8,361.79)
PAD48482	140,000# (KG63,504)	55,000# (KG24,948)	48" (C121.92)	48" (C121.92)	2" (C5.08)	160.0# (KG72.58)	2304 (CT14,865.4)

*8" X 10" OUTRIGGER LEG APPLIED UNDER TWO SEPARATE CONDITIONS: 10,000# VERTICALLY & 10,000# WITH A 45° ANGLE.
 **HANDLE LOCATED ON WIDTH SIDE OF ALL PADS. PADS 900 SQ. IN. & LARGER HAVE 2 OR MORE HANDLES OPPOSITE EACH OTHER.
 ***CUSTOM SIZE PADS ARE AVAILABLE. REQUIRES A MINIMUM ORDER. LEAD TIME FOR NON-STOCK ITEMS IN 30-45 DAYS
 KEY: C = CENTIMETERS; KG = KILOGRAMS; CT = SQUARE CENTIMETERS

Safety Tech Pad Features

- RELIABLE LOAD DISTRIBUTION
- LIGHTWEIGHT
- SAFETY TEXTURING
- MEMORY RECOVERY
- LIFETIME GUARANTEE

MAKE YOUR SETUP SAFE.

NOTICE

- FOOT PADS MUST BE SMOOTH AND HAVE 80 SQ. IN. OF SURFACE
- MUDDY OR LOOSE SOIL CONDITIONS MAY REQUIRE ADDITIONAL SHORING OR STACKING OF PADS
- EXCESSIVE FLEXING AND/OR BENDING MAY SHORTEN THE USABLE LIFE OF THE PAD.
- ACCEPTABLE OPERATING TEMPERATURE IS -40° TO 180° F

sales@alturnamats.com

Lifetime Guarantee
If you break it, we'll replace it. Guaranteed.

AlturnaMATS
701 East Spring St. Titusville, PA 16354
Office: 814.827.8884 Toll Free: 888.544.6287
Fax: 814.827.2903 Toll Free Fax: 866.723.2903